

ST TRACKED

HIGH PERFORMANCE STACKERS

The McCloskey ST TRACKED Stackers are all about efficiency, from its speedy setup time to its high degree of mobility, downtime is minimized while throughput and stockpile capacity are maximized.

Hydraulic main lift and top fold are standard, as is the diesel power unit. Electric and dual power are also available to get the job done, no matter what application. The 22.5 degree maximum conveyor angle allows for the highest stockpiles per conveyor length in the industry.

With its durable truss frame, large feed hopper and base production capacity of 500 TPH with optional upgrades to 800 TPH, the McCloskey ST TRACKED Stackers stand up well above the competition.



ST80T

RADIO REMOTE TRACK CONTROL

Provides remote maneuverability and enhances safety for moving freely to the best location.



HYDRAULIC TOP FOLD

Straightforward hydraulic controls to fold and unfold, raise and lower the conveyor.

HEAVY DUTY BELT

Conveyor built with Heavy Duty 36" - 3 ply- belt.



OPTIONAL V-BIN

Higher capacity over 7 yds³ V-Bin hopper allows for larger amounts of material to be directly loaded into the hopper with a loader or excavator and comes fitted with stabilizer legs.

OPTIONAL PADDLE WHEEL

This unit attaches to the top end of the head frame of the stacker and helps to mix material as it discharges from the conveyor.



OPTIONAL AUXILIARY GUARDING

This option attaches to the sides of the tail frame and improves safety by limiting exposure to moving parts.

OPTIONAL MAGNETIC SEPARATOR

This high powered magnet/conveyor combination attaches to the tail frame of the stacker and enables magnetic material separation from the source material.



ST80T

| | |
|------------------|---------------------------|
| Engine | Diesel or Electric |
| Transport Length | 51' 4" (15.6m) |
| Transport Height | 13' 2" (4.0m) |
| Transport Width | 8' 5" (2.6 m) |
| Stockpile Height | 31' 1" (9.47m) |
| Belt | 36" x 80' (900mm x 24.4m) |
| Production | 500 US TPH |



ST80TV

| | |
|------------------|---------------------------|
| Engine | Diesel or Electric |
| Transport Length | 52' (15.9m) |
| Transport Height | 11' 4" (3.4m) |
| Transport Width | 8' 5" (2.6 m) |
| Stockpile Height | 31' 1" (9.47m) |
| Belt | 36" x 80' (900mm x 24.4m) |
| Production | 800 US TPH |

ST100T

| | |
|------------------|----------------------------|
| Engine | Diesel or Electric |
| Transport Length | 70' 6" (21.5m) |
| Transport Height | 13' 6" (4.1m) |
| Transport Width | 8' 5" (2.6 m) |
| Stockpile Height | 41' 3" (12.5m) |
| Belt | 36" x 100' (900mm x 30.9m) |
| Production | 500 US TPH |



ST100TV

| | |
|------------------|----------------------------|
| Engine | Diesel or Electric |
| Transport Length | 70' 4" (21.4m) |
| Transport Height | 13' 6" (4.1m) |
| Transport Width | 8' 5" (2.57 m) |
| Stockpile Height | 41' 3" (12.5m) |
| Belt | 36" x 100' (900mm x 30.9m) |
| Production | 800 US TPH |