

CAT C2.2 generator set.



Image may not reflect actual generator set offered.

Technical specification for C2.2 Heat Exchanger cooled open generator set with rating 19,5 ekW @ 1800rpm 60Hz

GENSET SPECIFICATIONS	Project no	
CAT C2.2 19,5ekW	Yard no	
CAT GENERATOR 19,5ekW 60Hz	Date	

Caterpillar diesel engine, type **C2.2**, a 4-stroke, 4-cylinder indirect injection Inline-engine, naturally aspirated

1.0	Basic model	
1.1	Caterpillar model	C2.2 DINA
1.2	Rating	19,5 ekW ±3% ¹⁾ at 1800 rpm
1.3	Specification	4-stroke, electronically indirect injection Inline-engine naturally aspirated
1.4	Rotation	SAE standard, CCW viewed towards flywheel
1.5	Dimensions	Displacement:2,2 litersBore:84 mmStroke:100 mm
1.6	Dry weight	390 kg WO Sound Enclosure
1.7	Voltage	Generator voltage: 3 x 220/440V 60Hz

Note¹⁾

Engine performance is corrected to inlet air standard conditions of 99kPa and 25 °C. These values correspond to the standard atmospheric pressure and temperature in accordance with SAE J1995. Also included is a correction to standard fuel gravity and 35 degrees API having a lower heating value of 42,780kJ/kg when used at 29 °C where the density is 838,9 g/l.

2.0	Generator	
2.1	Generator	CAT
2.2	Generator	IP 23
	specifications	220/440V 60Hz
		24 KVA
		PF: 0,8
		Max ambient temp 45 deg C
2.3	Cooling	IP23 air cooled
2.4	Bearings	Roller bearing NDE
2.5	AVR	Solid state analogue voltage regulator

3.0	Cooling system	
3.1	Cooling system	Heat exchanger cooled
3.2	HT Cooling system	Belt driven HT pump, centrifugal type
		Gear driven SW pump
		Integrated tube and shell heat exchanger
		Expansion tank
3.3	Yard Supplied	Cooling Water Equipment
		SW supply
		All external piping and valves

	GENSET SPECIFICATIONS	Project no	
POO PAT	CAT C2.2 19,5ekW	Yard no	
	CAT GENERATOR 19,5ekW 60Hz	Date	

4.0	Exhaust system	
4.1	Exhaust	Maximum design backpressure 4,5kPa.
	specifications	Dry exhaust system
4.2	Exhaust manifold	Weld flange and gasket
4.3	Optional	Dry exhaust silencers available on request
		Ask for quote.

5.0	Air Inlet system	
5.1	Air Inlet specifications	Max air inlet temp 45 deg C
5.2	Air Cleaners	Dry type air cleaners included

6.0	Fuel system	
6.1	Fuel system	Mechanical engine pump with fuel injectors and glow plugs
6.2	Fuel specifications	Fuel type according to ISO8217, DMA/DMB/DMC (MGO/MDO)
6.3	Fuel lines	Double wall fuel lines With mounted alarm reservoir. Provides installed alarm reservoir.
6.4	Fuel Filters	Simplex engine filters with manual priming pump.
6.5	Shipped loose	Primary fuel FLTR/Water separator with NPT and BSP connections

7.0	Lube oil system	
7.1	Lube oil system	Closed system and closed crankcase ventilation. Oil filler and dipstick
7.2	Lube specifications	According to Cat specifications
7.3	Lube oil Filters	Engine oil filters
7.4	Shipped loose	Oil Pan Drain Pump - Brass with 3/8" BSP male connection

8.0	Starting system	
8.1	Starting system	Electric Starting motor
8.2	Starting motor	24V Starting motor
	specifications	Negative isolated ground electric system
8.3	Yard Supply	Starting equipment
		Set of batteries
		Battery charger

9.0	Engine control system	
9.1	Engine control system	Electronic governor

 GENSET SPECIFICATIONS	Project no	
CAT C2.2 19,5ekW	Yard no	_
CAT GENERATOR 19,5ekW 60Hz	Date	

10.0	Instrumentation	
10.1	Control system	CAT Deluxe Instrument Panel 24V
		Local start/stop and alarms
10.2	Shipped loose	Harness from engine to remote mounted CAT Deluxe instrument panel. 6 m
10.3	Yard supply	24V DC 10A power supply

11.0	Mounting system	
11.1	Mounting system	Engine and generator resiliently mounted to a common baseframe for fixed assembly towards ship structure.
11.2	Coupling specifications	Coupling plate

12.0	Paint	
12.1	Engine paint	Caterpillar Matterhorn white

13.0	Tests	
13.1	Engine tests	Engine Test at 100 and 10% Overload including Start Stop
		Retrospective Engine Certification is not possible.

14.0	Society Approval	
14.1	Certificates	NA Type Approval not required below 37kW. PC not available
14.2	Environmental certificates	NA No EIAPP needed below 130kW